

XI'AN FUNCTION MATERIAL GROUP CO., LTD Material Safety Data Sheet Copper Germanium Selenide

1. Product and Company Identification		
Trade Name: Chemical Formula:	Copper germanium selenide CuGeSe	
Manufacturer/Supplier:	XI'AN FUNCTION MATERIAL GROUP CO., LTD	
Street:	No. 69, Gazelle Valley, High-Tech Zone	
City:	XI'AN	
State: Zip Code:	Shaanxi 710077	
Country:	China	
Tel #:	+86-29-88993870/+86-13519132051	
	2. Hazards Identification	
Signal Word:	Danger	
Hazard Statements:	H301+H331: Toxic if swallowed or if inhaled	
	H373: May cause damage to organs through prolonged or repeated exposure	
Precautionary Statements:	P260: Do not breathe dust/fume/gas/mist/vapours/spray P301+P310: IF SWALLOWED: Immediately call a POISON CENTE.	
	or doctor/physician	
	P304+P340: IF INHALED: Remove victim to fresh air and keep at res in a position comfortable for breathing P405: Store locked up	
	P501: Dispose of contents/container in accordance with	
	local/regional/national/international regulations	
HMIS Health Ratings (0-4):		
Health:	2	
Flammability: Physical:	0 1	
	3. Composition	
Chemical Family:	Semimetallic alloy	
Additional Names:	None	
Copper germanium selenide (CuGeSe):	100	
Percentage: CAS #:	100 wt%	
EC #:	137904-21-3 NIL	
$L \subset \pi$.		

	4. First Aid Procedures
General Treatment:	Seek medical attention if symptoms persist.
Special Treatment:	None
Important Symptoms:	None
Inhalation:	Remove victim to fresh air. Supply oxygen if breathing is difficult.
Ingestion:	Seek medical attention
Skin:	Wash affected area with mild soap and water. Remove any
Evos:	contaminated clothing. Flush eyes with water, blinking often for several minutes. Remove
Eyes:	contact lenses if present and easy to do. Continue rinsing
	5. Firefighting Measures
Flammability:	Non-flammable, except as powder
Extinguishing Media:	Do not use water for metal fires – use CO ₂ , sand, extinguishing powder
Spec. Fire Fighting Procedure:	Use full-face, self-contained breathing apparatus with full protective
	clothing to prevent contact with skin and eyes. See section 10 for decomposition products.
	6. Accidental Release Measures
If Material Is Released/Spilled:	Wear appropriate respiratory and protective equipment specified in
	special protection information. Isolate spill area and provide
	ventilation. Vacuum up spill using a high efficiency particulate
	absolute (HEPA) air filter and place in a closed container for disposal. Take care not to raise dust.
Environmental Precautions:	Isolate runoff to prevent environmental pollution.
Environmental Precations.	isolate ranon to prevent environmental pontition.
	7. Handling and Storage
Handling Conditions:	Wash thoroughly after handling.
Storage Conditions:	Store in a cool dry place in a tightly sealed container. Store apart from
	materials and conditions listed in section 10.
Work/Hygienic Maintenance:	Do not use tobacco or food in work area. Wash thoroughly before eating and smoking. Do not blow dust off clothing or skin with
	compressed air.
Ventilation:	Provide sufficient ventilation to maintain concentration at or below threshold limit.
8.1	Exposure Controls and Personal Protection
Permissible Exposure Limits:	0.2 mg/m ³ as Se, long-term value
Threshold Limit Value:	0.2 mg/m ³ as Se, long-term value
Special Equipment:	None
Respiratory Protection:	Dust Respirator
Protective Gloves:	Rubber gloves
Eye Protection:	Safety glasses or goggles
Body Protection:	Protective work clothing. Wear close-toed shoes and long sleeves/pants.

9. Physical and Chemical Characteristics		
Color	N/A	
Form:	Pieces	
Odor:	Odorless	
Water Solubility:	Insoluble	
Boiling Point:	N/A	
Melting Point:	N/A	
Flash Point:	N/A	
Autoignition Temperature:	N/A	
Density:	N/A	
Molecular weight:	N/A	
	10. Reactivity	
Stability:	Stable under recommended storage conditions	
Reacts With:	Oxidizing agents	
Incompatible Conditions:	None	
Hazardous Decomposition Products:	Metal oxide fume, Selenium dioxide (SeO ₂)	
	11. Toxicological Information	
Potential Health Effects:		
Eyes:	May cause irritation	
Skin:	May cause irritation	
Ingestion:	May cause irritation	
Inhalation:	May cause irritation	
Chronic:	Selenium may cause amyotropic lateral sclerosis, bronchial irritation, gastrointestinal distress, vasopharyngeal irritation, garlic odor on breath and sweat, metallic taste, pallor, irritability, excessive fatigue, loss of fingernails and hair, pulmonary edema, anemia and weight loss. Copper compounds may be irritating to the skin, eyes and respiratory	
	tract. They may cause metal fume fever, hemolysis of the red blood cells and injury to the liver, lungs, kidneys, and pancreas. Ingestion may also cause vomiting, gastric pain, dizziness, anemia, cramps, convulsions, shock, coma, and death. Germanium compounds generally have a low order of toxicity. The anion and compound reactivity may contribute the greater part of the toxicity.	
Signs & Symptoms: Aggravated Medical Conditions:	N/A N/A	
Median Lethal Dose:	N/A	
Carcinogen:	IARC-3: Not classifiable as to carcinogenicity to humans. EPA-D: Not classifiable as to human carcinogenicity: inadequate human and animal evidence of carcinogenicity or no data are available.	

	12. Ecological Information
Aquatic Toxicity:	High
Persistent Bioaccumulation Toxicity:	No
Very Persistent, Very Bioaccumulative:	No
Notes:	Very toxic for aquatic organism.
	May cause long lasting harmful effect on aquatic life.
	Do not allow material to be released to the environment without prope
	governmental permits.
	Do not allow product to reach any water sources. Danger to drinking water if even extremely small quantities leak into
	the ground.
	Also poisonous for fish and plankton in water bodies.
	Avoid transfer into the environment.
	13. Disposal Considerations
Dispose of in accordance with local, stat	e, national, and international regulations.
	14. Transportation Data
	1
Hazardous:	Hazardous for transportation
Hazardous:	
	Hazardous for transportation Poison 6
Hazard Class:	Hazardous for transportation Poison 6 6.1 toxic substances
Hazard Class: Packing Group:	Hazardous for transportation Poison 6 6.1 toxic substances III
Hazardous: Hazard Class: Packing Group: UN Number: Proper Shipping Name:	Hazardous for transportation Poison 6 6.1 toxic substances
Hazard Class: Packing Group: UN Number:	Hazardous for transportation Poison 6 6.1 toxic substances III UN3283
Hazard Class: Packing Group: UN Number: Proper Shipping Name:	Hazardous for transportation Poison 6 6.1 toxic substances III UN3283 Selenium compound, solid, n.o.s. (Copper germanium selenide)
Hazard Class: Packing Group: UN Number: Proper Shipping Name: Sec 302 Extremely Hazardous: Sec 304 Reportable Quantities:	Hazardous for transportation Poison 6.1 toxic substances III UN3283 Selenium compound, solid, n.o.s. (Copper germanium selenide) 15. Regulatory Information
Hazard Class: Packing Group: UN Number: Proper Shipping Name: Sec 302 Extremely Hazardous:	Hazardous for transportation Poison 6.1 toxic substances III UN3283 Selenium compound, solid, n.o.s. (Copper germanium selenide) 15. Regulatory Information No

This safety data sheet should be used in conjunction with technical sheets. It does not replace them. The information given is based on our knowledge of this product, at the time of publication. It is given in good faith. The attention of the user is drawn to the possible risks incurred by using the product for any other purpose other than that for which it was intended. This does not in any way excuse the user from knowing and applying all the regulations governing his activity. It is the sole responsibility of the user to take all precautions required in handling the product. The aim of the mandatory regulations mentioned is to help the user to fulfill his obligations regarding the use of hazardous products.

Document Last Revised:

06/25/2016